



On Load Tap Changer  
Voltage Stabiliser

# Orion Plus

three-phase  
**30-1250kVA**



## Standard features

<b>Voltage stabilisation</b>	Independent phase control
<b>PC adjustable output voltage (at 400V rated voltage)</b>	from 210V to 255V (L-N) / from 360V to 440V (L-L)
<b>Frequency</b>	50/60Hz $\pm$ 5%
<b>Admitted load variation</b>	Up to 100%
<b>Admitted load imbalance</b>	100%
<b>Cooling</b>	Natural air ventilation (aided with fans over 45°C)
<b>Ambient temperature</b>	-25/+45°C
<b>Storage temperature</b>	-25/+60°C
<b>Max relative humidity</b>	95%
<b>Admitted overload</b>	200% 2 min.
<b>Harmonic distortion</b>	None introduced
<b>Colour</b>	RAL 7035
<b>Protection degree</b>	IP21
<b>Instrumentation</b>	Input & output digital multimeter
<b>Installation</b>	Indoor
<b>Overvoltage protection</b>	– Output class II surge arrestor – Soft start through supercapacitors in case of blackout

# PRICE LIST

January 2016



**Orion Plus**  
three-phase  
**30-1250kVA**

Type	Input voltage variation range	Rating	Weight	Price
	[%]	[kVA]	[kg]	AED
Input voltage variation range <b>±30%/±25%</b>				
<b>90-30</b>	±30	90		
<b>105-25</b>	±25	105	760	12,970.00
<b>105-30</b>	±30	105	800	13,550.00
<b>120-25</b>	±25	120		
<b>120-30</b>	±30	120	850	14,270.00
<b>135-25</b>	±25	135		
<b>150-30</b>	±30	150	900	14,990.00
<b>200-25</b>	±25	200		
<b>200-30</b>	±30	200	1300	20,760.00
<b>250-25</b>	±25	250		
<b>250-30</b>	±30	250	1400	22,210.00
<b>300-25</b>	±25	300		
<b>300-30</b>	±30	300	1600	25,090.00
<b>400-25</b>	±25	400		
<b>400-30</b>	±30	400	2000	30,860.00
<b>500-25</b>	±25	500		